



Nadellager NA48 mit Borden, mit Innenring, ohne Dichtung



NA48

axialer Verschiebeweg „s“

Maßtable - Abmessungen in mm

Haupt- abmessungen			Tragzahlen		Ermüdungs- grenz- belastung	Grenz- dreh- zahl	Bezugs- dreh- zahl	Gewicht	Kurzeichen	Abmessungen		
			dyn.	stat.						F	r	s
d	D	C	C _r N	C _{0r} N	C _{ur} N	n _G min ⁻¹	n _B min ⁻¹	m ≈ g			min.	
110	140	30	106.000	216.000	36.000	3.900	2.270	1.080	NA4822	120	1,0	0,80
120	150	30	112.000	239.000	39.000	3.600	2.070	1.170	NA4824	130	1,0	0,80
130	165	35	134.000	310.000	48.500	3.250	1.930	1.810	NA4826	145	1,1	1,00
140	175	35	136.000	325.000	50.000	3.050	1.810	1.920	NA4828	155	1,1	1,00
150	190	40	172.000	400.000	62.000	2.850	1.780	2.720	NA4830	165	1,1	1,50
160	200	40	181.000	435.000	66.000	2.700	1.650	2.890	NA4832	175	1,1	1,50
170	215	45	209.000	510.000	75.000	2.550	1.610	3.960	NA4834	185	1,1	1,50
180	225	45	219.000	550.000	80.000	2.420	1.490	4.200	NA4836	195	1,1	1,50
190	240	50	255.000	690.000	100.000	2.250	1.330	5.610	NA4838	210	1,5	1,50
200	250	50	260.000	720.000	102.000	2.150	1.250	5.840	NA4840	220	1,5	1,50
220	270	50	275.000	790.000	110.000	1.980	1.110	6.380	NA4844	240	1,5	1,50
240	300	60	400.000	1.080.000	150.000	1.780	960	10.000	NA4848	265	2,0	2,00
260	320	60	415.000	1.160.000	158.000	1.660	870	10.600	NA4852	285	2,0	2,00
280	350	69	510.000	1.300.000	175.000	1.540	840	15.300	NA4856	305	2,0	2,50
300	380	80	700.000	1.770.000	235.000	1.420	720	21.800	NA4860	330	2,1	2,00
320	400	80	710.000	1.850.000	242.000	1.340	670	23.000	NA4864	350	2,1	2,00
340	420	80	730.000	1.940.000	249.000	1.270	620	24.200	NA4868	370	2,1	2,00
360	440	80	740.000	2.020.000	255.000	1.210	590	25.600	NA4872	390	2,1	2,00
380	480	100	1.130.000	2.900.000	370.000	1.130	510	42.600	NA4876	415	2,1	2,00

1) Mit Verschlussringen, ohne Schmierbohrung und ohne Schmierrille.