


Nadel-Schräggugellager NKIA, mit Innenring, einseitig wirkend




NKIA

Maßtabelle - Abmessungen in mm

Haupt- abmessungen			Tragzahlen				Ermüdungs- grenzbelastung		Grenz- dreh- zahl	Bezugs- dreh- zahl	Gewicht	Kurzzzeichen			
d	D	B	radial		axial		C _{ur}	C _{ua}	n _G	n _B	m				
			dyn.	stat.	dyn.	stat.									
			C _r	C _{0r}	C _a	C _{0a}	N	N							
12	24	16	8.600	8.300	2.700	3.450	1.630	152	23.600	21.000	40	NKIA5901			
15	28	18	12.000	13.600	2.900	4.200	2.430	186	21.600	17.000	50	NKIA5902			
17	30	18	12.400	14.600	3.150	4.900	2.600	216	20.600	15.000	56	NKIA5903			
20	37	23	23.700	25.500	4.900	7.400	4.600	330	17.200	14.000	103	NKIA5904			
22	39	23	26.000	29.500	5.300	8.600	5.300	380	16.100	12.000	118	NKIA59/22			
25	42	23	26.500	31.500	5.400	9.300	5.700	410	14.600	12.000	130	NKIA5905			
30	47	23	28.500	35.500	5.900	11.200	6.400	495	12.700	10.000	147	NKIA5906			
35	55	27	35.500	50.000	7.400	14.900	9.400	660	10.900	9.000	243	NKIA5907			
40	62	30	48.500	67.000	9.200	19.400	11.500	860	9.600	7.500	315	NKIA5908			
45	68	30	51.000	73.000	9.600	21.400	12.600	950	8.700	7.000	375	NKIA5909			
50	72	30	53.000	80.000	10.100	24.300	13.800	1.080	8.000	6.500	380	NKIA5910			
55	80	34	65.000	100.000	12.100	29.500	17.300	1.300	7.300	6.000	550	NKIA5911			
60	85	34	68.000	108.000	12.400	32.000	18.800	1.410	6.800	5.500	590	NKIA5912			
65	90	34	69.000	112.000	12.800	34.000	19.500	1.510	6.300	5.500	635	NKIA5913			
70	100	40	95.000	156.000	16.800	44.500	27.500	1.970	5.800	4.900	980	NKIA5914			

Nadel-Schräggugellager NKIA, mit Innenring, einseitig wirkend



NKIA

Abmessungen				
d	F	C	r	
			min.	
12	16	—	0,3	
15	20	—	0,3	
17	22	—	0,3	
20	25	—	0,3	
22	28	—	0,3	
25	30	—	0,3	
30	35	—	0,3	
35	42	—	0,6	
40	48	—	0,6	
45	52	—	0,6	
50	58	—	0,6	
55	63	—	1,0	
60	68	—	1,0	
65	72	—	1,0	
70	80	—	1,0	