


Nadel-Schrägkugellager NKIB, mit Innenring, zweiseitig wirkend




NKIB

Maßtable - Abmessungen in mm

Haupt-abmessungen			Tragzahlen				Ermüdungs-grenzbelastung		Grenz-dreh-zahl	Bezugs-dreh-zahl	Gewicht	Kurzzeichen	
d	D	B	radial		axial		C_{Ur}	C_{Ua}	n_G	n_B	m		
			dyn. C_r N	stat. C_{0r} N	dyn. C_a N	stat. C_{0a} N							
12	24	18	8.600	8.300	2.700	3.450	1.630	152	23.600	21.000	43	NKIB5901	🌐🛒📦
15	28	20	12.000	13.600	2.900	4.200	2.430	186	21.600	17.000	52	NKIB5902	🌐🛒📦
17	30	20	12.400	14.600	3.150	4.900	2.600	216	20.600	15.000	58	NKIB5903	🌐🛒📦
20	37	25	23.700	25.500	4.900	7.400	4.600	330	17.200	14.000	107	NKIB5904	🌐🛒📦
22	39	25	26.000	29.500	5.300	8.600	5.300	380	16.100	12.000	122	NKIB59/22	🌐🛒📦
25	42	25	26.500	31.500	5.400	9.300	5.700	410	14.600	12.000	134	NKIB5905	🌐🛒📦
30	47	25	28.500	35.500	5.900	11.200	6.400	495	12.700	10.000	151	NKIB5906	🌐🛒📦
35	55	30	35.500	50.000	7.400	14.900	9.400	660	10.900	9.000	247	NKIB5907	🌐🛒📦
40	62	34	48.500	67.000	9.200	19.400	11.500	860	9.600	7.500	320	NKIB5908	🌐🛒📦
45	68	34	51.000	73.000	9.600	21.400	12.600	950	8.700	7.000	380	NKIB5909	🌐🛒📦
50	72	34	53.000	80.000	10.100	24.300	13.800	1.080	8.000	6.500	385	NKIB5910	🌐🛒📦
55	80	38	65.000	100.000	12.100	29.500	17.300	1.300	7.300	6.000	555	NKIB5911	🌐🛒📦
60	85	38	68.000	108.000	12.400	32.000	18.800	1.410	6.800	5.500	595	NKIB5912	🌐🛒📦
65	90	38	69.000	112.000	12.800	34.000	19.500	1.510	6.300	5.500	640	NKIB5913	🌐🛒📦
70	100	45	95.000	156.000	16.800	44.500	27.500	1.970	5.800	4.900	985	NKIB5914	🌐🛒📦

Nadel-Schrägkugellager NKIB, mit Innenring, zweiseitig wirkend



NKIBFehler! Textmarke nicht definiert.

Abmessungen				
d	F	C	r	
			min.	
12	16	16	0,3	
15	20	18	0,3	
17	22	18	0,3	
20	25	23	0,3	
22	28	23	0,3	
25	30	23	0,3	
30	35	23	0,3	
35	42	27	0,6	
40	48	30	0,6	
45	52	30	0,6	
50	58	30	0,6	
55	63	34	1,0	
60	68	34	1,0	
65	72	34	1,0	
70	80	40	1,0	