


Toroidalrollenlager mit kegeliger Bohrung (Kegel 1:30), vollrollig



C40-K30-V



kegelige Bohrung

Maßtabelle - Abmessungen in mm

Haupt- abmessungen			Tragzahlen		Ermüdungs- grenzbelastung	Grenz- drehzahl	Bezugs- drehzahl	Gewicht	Kurzzeichen
			dyn.	stat.					
d	D	B	C _r kN	C _{0r} kN	C _{ur} kN	n _G min ⁻¹	n _B min ⁻¹	m ≈ kg	
65	100	35	197	285	34	3.050	–	0,95	C4013-K30-V   
75	115	40	209	355	40	2.470	–	1,00	C4015-K30-V   
100	150	50	355	530	66	1.580	–	2,94	C4020-K30-V   
110	170	60	510	800	89	1.320	–	4,74	C4022-K30-V   
120	180	60	550	890	99	1.120	–	5,08	C4024-K30-V   
130	200	69	730	1.130	119	990	–	7,49	C4026-K30-V   
140	210	69	760	1.220	126	890	–	7,95	C4028-K30-V   
150	225	75	780	1.320	132	810	–	9,91	C4030-K30-V   
160	240	80	910	1.470	158	740	–	12,00	C4032-K30-V   
170	260	90	1.140	1.880	187	650	–	16,40	C4034-K30-V   
180	280	100	1.330	2.140	212	600	–	21,60	C4036-K30-V   
190	290	100	1.370	2.330	221	540	–	22,60	C4038-K30-V   
200	310	109	1.650	2.650	265	490	–	28,70	C4040-K30-V   
220	340	118	1.960	3.250	285	425	–	37,30	C4044-K30-V   